RUBBERFORM RECYCLED PRODUCTS, LLC

RUBBERFOAM RECYCLED PRODUCTS LLC
75 MICHIGAN ST
LOCKPORT, NY 14094-2629
PHONE: (716) 478-0404
FAX: (716) 478-0408
www.rubberform.com

SELECT DESIRED REFLECTIVE POLYGON COLOR:

- [x] SAFETY YELLOW
- [ ] EMERGENCY VEHICLE RED
- [ ] HANDICAP BLUE
- [ ] ECO-GREEN
- [ ] WHITE



SPECIFICATIONS:
- 38 LBS.
- 4" H x 6" W x 72" L.
- 8 LARGE POLYGON STRIPES MADE FROM RECYCLED PLASTIC.
- 5 MOORING HOLES GOT LAG BOLTS OR REBAR.

NOTES:
1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER C4.0 18172-DET

PARKING LOT WHEEL STOPS

PARKING LOT WHEEL STOPS

C4.0 18172-DET — REVISION DATE 21/11/2018

PROTECTED BY COPYRIGHT ©2018 CADDETAILS.COM LTD. CADdetails.com



NOTE (R7-8 SIGN): THIS IS A STANDARD SIGN AND MAY BE ORDERED FROM ANY TRAFFIC SIGN SUPPLIER BY NUMBER. THE SIGN MUST BE SUPPLEMENTED WITH A "VAN ACCESSIBLE" SIGN AS APPLICABLE AND/OR AMOUNT OF THE FINE FOR ILLEGALLY PARKING IN THE RESERVED SPACE(S) A MUNICIPALITY MAY IMPOSE. CONFIRM WITH LOCAL REGULATIONS.



ACCESSIBILITY SIGNAGE
NO SCALE



VERTICAL CURB DETAIL
NO SCALE



CONCRETE SIDEWALK
NO SCALE



Work under this item shall include cutting out the existing bituminous surface to a minimum depth and width as shown, so the new surface may heel into the existing surface. The contract unit price bid per linear foot for "EDGE KEY" shall include all necessary materials, labor, equipment, etc. to perform the work and dispose of the bituminous material removed.

FLEXIBLE PAVEMENT SAWCUT EDGE KEY DETAIL
NO SCALE



BITUMINOUS PAVEMENT

NOTE: SECTION PER GEOTECH REPORT BY TERRACON ON MAY 31, 2018.

ALL PAVING MATERIALS MUST COMPLY WITH THE CURRENT KENTUCKY DEPARTMENT OF HIGHWAYS SPECIFICATIONS. THE GRANULAR BASE MUST BE COMPACTED TO AT LEAST 98 PERCENT OF THE STANDARD PROCTOR MAXIMUM DRY DENSITY (ASTM D-698).

BITUMINOUS PAVEMENT SECTION DETAIL
NO SCALE



NOTE:
CONCRETE PAVING SHALL MEET THE REQUIREMENTS OF THE KENTUCKY DEPT. OF TRANSPORTATION SPECIFICATIONS, LATEST EDITION.

HEAVY DUTY CONCRETE/DRIVE LANES
NO SCALE



NOTE:
CONCRETE PAVING SHALL MEET THE REQUIREMENTS OF THE KENTUCKY DEPT. OF TRANSPORTATION SPECIFICATIONS, LATEST EDITION.

HEAVY DUTY CONCRETE/DUMPSTER PAD
NO SCALE



MEASUREMENT OF CURB RAMP SLOPE



CURB RAMP

"X" IS 60" MIN. AT AN OUT SWING DOOR WITH A SLOPE OF 1:50 (2%) MAXIMUM. LEVEL SURFACE IS PREFERED.

SIDE FLARE NOTE: (SEE REFERENCE DIAGRAM ABOVE). SIDE FLARES SHALL HAVE A MAXIMUM SLOPE OF 1:10 (10%). WHERE "X" IS LESS THAN 48", SIDE FLARE SLOPE SHALL BE 1:12 (8.33%) MAXIMUM. WHERE "X" IS LESS THAN 36".



"IN-LINE" RAMP

NOTES: A CURB RAMP(S) MUST BE PROVIDED ALONG ALL ACCESSIBLE PATHS.

A RAMP IS ANY SLOPE GREATER THAN 1:20 (5%) AND SHALL HAVE A MAXIMUM SLOPE OF 1:12 (8.33%). THE MAXIMUM SLOPE IS 1" OF RISE PER FOOT OF DISTANCE TRAVELED. ALL SLOPED AREAS OF THE RAMP ARE TO CONSIST VISUALLY FROM ADJOINING SURFACES.

THE CLEAR WIDTH OF ANY RAMP IS A MINIMUM OF 36".

CURB RAMPS HAVE A MAXIMUM RISE OF 6" AND DO NOT REQUIRE HANDRAILS. ANY RAMP WITH GREATER THAN A 6" RISE SHALL HAVE HANDRAILS ON BOTH SIDES AND CURBED EDGE PROTECTION ON BOTH SIDES. EDGE PROTECTION CONSISTS OF CURBS, WALLS, RAILINGS, OR PROJECTING SURFACES THAT PREVENT PEOPLE FROM SLIPPING OFF THE RAMP. HANDRAIL DETAILS SHALL FOLLOW ACCESSIBLE GUIDELINES.

CURB RAMPS
NO SCALE

PANDA EXPRESS, INC.
1683 Walnut Grove Ave.
Rosemead, California
91770
Telephone: 626.799.9898
Facsimile: 626.372.8288

All ideas, designs, arrangement and plans indicated or represented by this drawing are the property of Panda Express Inc. and were created for use on this specific project. None of these ideas, designs, arrangements or plans may be used by or disclosed to any person, firm, or corporation without the written permission of Panda Express Inc.

REVISIONS:

ISSUE DATE:

1st	PERMIT	10-5-18
2nd	BID SET	11-20-18

DRAWN BY:XG

PANDA PROJECT #: S8-19-D6462
ARCH PROJECT #: 18044.013
CIVIL PROJECT #: 18172

LD&D
LAND DESIGN & DEVELOPMENT, INC.
ENGINEERING • LAND SURVEYING • LANDSCAPE ARCHITECTURE
529 WASHBURN AVENUE, SUITE 101 LOUISVILLE, KENTUCKY 40222
PHONE: 502-814-9934
WEB SITE: WWW.LDD-INC.COM

khcklover architect
10955 LOWELL AVENUE, SUITE 700
OVERLAND PARK, KS 66210
ph: 913.649.8181 • fx: 913.649.1275

PANDA EXPRESS

TRUE WARM & WELCOME 2200
Conestoga Pkwy & Historical Trail
Shepherdsville, KY, 40165

DETAILS

C4.0

BID SET 11.20.18

TRUE WARM & WELCOME 2200